

Tel: +27 12 803 8595
Fax: +27 12 803 8462
Customer care line: 086 1554 321
e-mail: timberlife@icon.co.za
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD
REG No 2000/017132/07

PO Box 73117, Lynnwood Ridge, 0040
31 Axle Street
Silverton Ext 52
Pretoria, South Africa



PRODUCT DATA SHEET

Furni-Floor

Product Name: FURNI-FLOOR

Product Type: WATER-BORNE FLOOR QUALITY VARNISH FOR INTERIOR TIMBERS (Latest water-based technology)

Description: **Furni-Floor** is a clear, water-borne varnish that provides a durable gloss finish with excellent wear resistance for use on interior wooden floors and timbers. It is quick drying and virtually odourless. After full curing, it provides a tough but flexible finish that resists scratching, staining and seals wood against water penetration. It is solvent free and non-flammable.

Furni-Floor is therefore particularly suitable for use as a high quality clear coating on interior wooden floors, furniture, bar tops, stairs and stair railings, skirting boards, cladding, cupboards, etc.

Active Ingredients: Pure acrylic polymers and special cross-linking additives.

Physical Characteristics:	Appearance	- Milky white liquid
	Solubility	- Waterborne
	Density @ 20°	- 1,036 kg/l

Use Restriction: Only for use on interior timbers. Do not apply over any other coatings.

Application: Use brush or spray application methods. Mix contents before use. Dilute the first application 2 : 1 with water and use as a primer coat. Allow to dry for 2 to 6 hours depending on weather conditions, then sand lightly before applying a second coat undiluted. Allow to dry overnight and apply a third coat undiluted. Allow 24 hours drying/curing time before re-opening for traffic in the case of floors.

Note: Full curing is generally achieved after 4 to 7 days to ensure proper hardness and wear resistance.

Application Rate: $\pm 15 \text{ m}^2 - 20 \text{ m}^2$ per l per coat

Dilution Rates: Ready for use. Dilute only as indicated.

Storage: Storage temperatures should not exceed 40°C. Keep containers tightly closed.

Packaging: 1l, 5l, 20l, 25l and 200l containers.

Note: Clean equipment with water immediately after use.