

Tel: +27 12 803 8595  
Fax: +27 12 803 8462  
Customer care line: 086 1554 321  
e-mail: timberlife@icon.co.za  
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD  
REG No 2000/017132/07

PO Box 73117, Lynnwood Ridge, 0040  
31 Axle Street  
Silverton Ext 52  
Pretoria, South Africa



---

## PRODUCT DATA SHEET

## Pave-Cote

---

**Product Name:** PAVE-COTE

**Product Type:** TRANSPARENT EXTERIOR/INTERIOR PAVING SEALER

**Description:** **Pave-Cote** is a high performance, emulsion-based (solvent free) paving sealer for exterior and interior applications. The coating provides water repellency and a colourless sheen finish that protects paving from oil stains and grime.

**Pave-Cote** contains acrylic resins plus UV absorbers and light stabilizers that provide flexibility to the coated film and protect the coating against the harmful effect of sunlight.

*Not recommended for use on slate or slasto and heavy traffic areas.*

**Active Ingredients:** Acrylic resins, UV absorbers and light stabilizers, dry film mouldicide/algicide.

**Physical Characteristics:**

|                |                      |
|----------------|----------------------|
| Appearance     | - Milky white liquid |
| Solubility     | - Waterborne         |
| Density @ 20°C | - ± 1,04 kg/l        |

**Use Restriction:** For industrial and household use.

**Application:** Paint or roller brush, spray. Mix contents before use.

**Application Rate:** 5 to 10 m<sup>2</sup>/l depending on the porosity of the surface.

**Dilution Rates:** 2 parts **Pave-Cote** and 1 part of water.

**Storage:** Storage temperature should not exceed 40°C. Keep container tightly closed.

**Packaging:** 1l, 5l, 20l, 25l and 200l containers nett.

**Note:** Wash equipment with water immediately after use.