

Tel: +27 12 803 8595
Fax: +27 12 803 8462
Customer care line: 086 1554 321
e-mail: timberlife@icon.co.za
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD
REG No 2000/017132/07

PO Box 73117, Lynnwood Ridge, 0040
31 Axle Street
Silverton Ext 52
Pretoria, South Africa



PRODUCT DATA SHEET

UltraCare Gold

Product Name: ULTRACARE GOLD

Product Type: PENETRATING WATER REPELLENT, HIGH SHEEN WOOD FINISH FOR EXTERIOR AND INTERIOR USE

Description: **UltraCare Gold** is a penetrating water repellent sealer that has been specially formulated to protect outdoor timbers against the harsh South African climatic conditions.

It contains an unique blend of high quality drying oils, resins and water repellent wax components as well as high performance UV absorbers and light stabilizers. These ingredients are dissolved in a formulated solvent carrier to deeply penetrate, nourish and stabilize the wood and ensure exceptional protection against water uptake and UV degradation caused by sunlight exposure. It dries to a clear sheen finish that enhances the natural colour and beauty of the wood.

UltraCare Gold also contains insecticidal and fungicidal additives that provide added protection against wood borer and termite attack as well as mould growth and fungal discolouration, respectively.

UltraCare Gold can also be used as a clear finish on “**Stain**” penetrating wood colouring stains or can be tinted to various shades of brown: Mahogany, Oregon, Teak, Oak, Dark Oak, Golden Brown and Walnut. (Only use Timberlife “**Solv-Tints**” that contain high quality, colour fast UV resistant transparent iron oxide pigments).

Ideal for use on wooden window and door frames, doors, balustrades, etc. where a high sheen finish is preferred. **Not recommended for** use on high traffic areas such as wooden decks and floors.

Active Ingredients: Drying oils, Resins, Waxes UV absorbers and Light stabilizers plus insecticides and Fungicides/Algicides.

Physical Characteristics:	Appearance	-	Transparent amber colour
	Solubility	-	Solvent borne
	Density @ 20°C	-	± 0,85 kg/l

Use Restriction: Not to be used on previously coated timber surfaces. Remove old coatings before application.

Application: Brush, roller brush or spray methods. Mix contents before use. Apply a liberal first coat and allow to dry for at least 4 to 6 hours. Sand lightly, apply a second coat and spread evenly. Allow to dry for 24 hours before applying a final coat. Wipe off all excess sealer after each application.

Application Rate: 5m² - 10m² per l per coat (depending on timber type).

Dilution Rates: Ready for use.

Storage: Storage temperatures should not exceed 40°C. Keep container sealed.

Packaging: 1l, 5l, 20l, 25l and 200l containers.

Caution: Flammable. Avoid open flames.

Z:\PDS MASTERS\ULTRA CARE GOLD PDS.doc

Rev 1.000

Rev Date: January 2006